

Overview

****For latest information on this product please use [HPE Ethernet 10GBASE-T Adapters QuickSpecs](#)****

HPE Ethernet 10Gb 2-port 562 Adapters

Extended SKU - This adapter is part of an extended catalog of products tailored for customers in specific markets or with specific workloads, requiring the utmost in performance or value, but typically have a longer lead-time.

The HPE Ethernet 10Gb 2-port 562 adapters (include HPE Ethernet 10Gb 2-port 562FLR-T Adapter and HPE Ethernet 10Gb 2-port 562T Adapter) for ProLiant servers are dual-port 10G BASE-T adapters featuring Intel X550 Controller in both FlexibleLOM (562FLR-T) and Stand up (562T) form factors. These adapters deliver full line-rate performance across all ports utilizing CAT 6A UTP cabling with distances up to 100 meters. Providing high performance Ethernet connectivity, it is ideal for virtual server and cloud computing environments. The HPE Ethernet 562 adapters can provide up to 40Gbps of bi-directional Ethernet bandwidth, helping to alleviate network bottlenecks.



HPE Ethernet 10Gb 2-port 562FLR-T Adapter



HPE Ethernet 10Gb 2-port 562T Adapter

Platform Information

Models

HPE Ethernet 10Gb 2-port 562FLR-T Adapter (Extended)	817745-B21
HPE Ethernet 10Gb 2-port 562T Adapter (Extended)	817738-B21

Kit Contents	HPE Ethernet 10Gb 2-port 562FLR-T Adapter
	Quick install card
	Product warranty statement
	HPE Ethernet 10Gb 2-port 562T Adapter
	Quick install card
	Product warranty statement
	Low-profile bracke

Compatibility

Supported Servers

- HPE ProLiant DL20 Gen10 Server (562T)
 - HPE ProLiant DL120 Gen10 Server (562FLR-T, 562T)
 - HPE ProLiant DL160 Gen10 Server (562FLR-T, 562T)
 - HPE ProLiant DL180 Gen10 Server (562FLR-T, 562T)
 - HPE ProLiant DL360 Gen10 Server (562FLR-T, 562T)
 - HPE ProLiant DL380 Gen10 Server (562FLR-T, 562T)
 - HPE ProLiant DL385 Gen10 Server (562FLR-T, 562T)
 - HPE ProLiant DL560 Gen10 Server (562FLR-T, 562T)
 - HPE ProLiant DL580 Gen10 Server (562FLR-T, 562T)
 - HPE Apollo 2000 XL170r Gen10 Server (562FLR-T, 562T)
 - HPE Apollo 2000 XL190r Gen10 Server (562FLR-T, 562T)
 - HPE Apollo 4500 XL450 Gen10 Server (562FLR-T, 562T)
 - HPE Apollo 6000 XL230k Gen10 Server (562T)
 - HPE Apollo 6500 XL270d Gen10 Server (562T)
 - HPE ProLiant ML30 Gen10 Server (562T)
 - HPE ProLiant ML110 Gen10 Server (562T)
 - HPE ProLiant ML350 Gen10 Server (562T)
- NOTE:** This is a list of supported servers. Some may be discontinued.

Standard Features

At a Glance Features	Dual 10Gb ports provide up to 40 Gb/s bi-directional Ethernet bandwidth Jumbo Frame FlexibleLOM (562FLR-T) and Stand up (562T) HPE Sea of Sensors 3D Tunnel Offload(NVGRE and VxLAN) Single-root input/output virtualizaton (SR-IOV) IPv6 Acceleration Preboot eXecution Environment (PXE) Wake on Lan (WOL)- (only 562FLR-T) Checksum & Segmentation Offload VMware NetQueue and Microsoft Virtual Machine Queue (VMQ) Precision Time Protocol (PTP) Data Plane Development Kit (DPDK)
Throughput-Theoretical Bandwidth	This adapter delivers 20 Gb/s bi-directional Ethernet transfer rate per port (40 Gb/s per adapter), providing the network performance needed to improve response times and alleviate bottlenecks.
Checksum & Segmentation Offload	Normally the TCP Checksum is computed by the protocol stack. Segmentation Offload is technique for increasing outbound throughput of high-bandwidth network connections by reducing CPU overhead. The technique is also called TCP segmentation offload (TSO) when applied to TCP, or generic segmentation offload (GSO).
DPDK	This adapter supports DPDK with benefit for packet processing acceleration and use in NFV deployments.
Form Factor	This adapter series offers both FlexibleLOM and Stand up.
HPE Sea Of Sensors 3D	Support for the HPE Sea of Sensors which is a collection of 32 sensors that automatically track thermal activity - heat - across the server. When temperatures get too high, sensors can initiate fans and make other adjustments to reduce energy usage. A significant improvement lies in the ability to apply fan speed increases only to the portion of the system that is rising in temperature, rather than all six fans in unison, which reduces the amount of energy used for cooling.
IPv6	IPv6 uses 128-bit addressing allowing for more devices and users on the internet. IPv4 supported 32-bit addressing.
Jumbo Frames	This adapter supports Jumbo Frames (also known as extended frames), permitting up to a 9,600 byte (KB) transmission unit (MTU) when running Ethernet I/O traffic. This is over six times the size of a standard 1500-byte Ethernet frame. With Jumbo Frames, networks can achieve higher throughput performance and greater CPU utilization. These attributes are particularly useful for database transfer and tape backup operations.
Management Support	This adapter ships with agents that can be managed from HPE Systems Insight Manager or other management application that support SNMP.

Standard Features

Preboot eXecution Environment (PXE)	Support for PXE enables automatic deployment of computing resources remotely from anywhere. It allows a new or existing server to boot over the network and download software, including the operating system, from a management/ deployment server at another location on the network. Additionally, PXE enables decentralized software distribution and remote troubleshooting and repairs.
Server Integration	This adapter is a validated, tested, and qualified solution that is optimized for HPE ProLiant servers. Hewlett Packard Enterprise validates a wide variety of major operating systems drivers with the full suite of web-based enterprise management utilities including HPE Intelligent Provisioning and HPE Systems Insight Manager that simplify network management. This approach provides a more robust and reliable networking solution than offerings from other vendors and provides users with a single point of contact for both their servers and their network adapters.
Single-Root I/O Virtualization	Single-Root I/O Virtualization (SR-IOV) provides a mechanism to bypass the host system hypervisor in virtual environments providing near metal performance and server efficiency. SR-IOV provides mechanism to create multiple Virtual Functions (VFs) to share single PCIe resources. The device is capable of SR-IOV, and requires Server BIOS support, controller firmware, and OS support.
Precision Time Protocol (IEEE 1588 PTP)	Synchronization of system clocks throughout a network, achieving clock accuracy in the sub-microsecond range, making it suitable for measurement and control systems.
Tunnel Offload	Minimize the impact of overlay networking on host performance with tunnel offload support for VXLAN, NVGRE and GENEVE. By offloading packet processing to adapters, customers can use overlay networking to increase VM migration flexibility and virtualized overlay networks with minimal impact to performance. HPE Tunnel Offloading increases I/O throughput, reduces CPU utilization, and lowers power consumption. Tunnel Offload supports VMware's VXLAN, Microsoft's NVGRE solutions and Generic Network Virtualization Encapsulation (GENEVE) solutions.
VMware NetQueue and Microsoft Virtual Machine Queue (VMQ)	VMware NetQueue is technology that significantly improves performance of 10 Gigabit Ethernet network adapters in virtualized environments. Windows Hyper-V VMQ (VMQ) is a feature available on servers running Windows Server 2008 R2 with VMQ-enabled Ethernet adapters. VMQ uses hardware packet filtering to deliver packet data from an external virtual machine network directly to virtual machines, which reduces the overhead of routing packets and copying them from the management operating system to the virtual machine.
Wake-on-LAN	This adapter provides Wake-on-LAN (WoL) support through the PCI Express bus. A system that supports Wake-on-LAN can remain available to the systems administrator during its normal downtime. Once the machine is awakened, the systems administrator can remotely control, audit, debug, or manage the machine.
Warranty	Maximum: The remaining warranty of the HPE product in which it is installed (to a maximum

Standard Features

three-year, limited warranty).

Minimum: One year limited warranty.

NOTE: Additional information regarding worldwide limited warranty and technical support is available at:

<http://h17007.www1.hpe.com/us/en/enterprise/servers/warranty/index.aspx#.V4e3tPkrJhE>

Service and Support

Service and Support	NOTE: This adapter is covered under HPE Support Services/ Service Contract applied to the HPE ProLiant Server or enclosure. No separate HPE Support Services need to be purchased. Most HPE branded options sourced from HPE that are compatible with your product will be covered under your main product support at the same level of coverage, allowing you to upgrade freely. Additional support is required on select workload accelerators, switches, racks and UPS options 12KVA and over. Coverage of the UPS battery is not included under HPE support services; standard warranty terms and conditions apply.
Warranty and Support Services	Warranty and Support Services will extend to include HPE options configured with your server or storage device. The price of support service is not impacted by configuration details. HPE sourced options that are compatible with your product will be covered under your server support at the same level of coverage allowing you to upgrade freely. Installation for HPE options is available as needed. To keep support costs low for everyone, some high value options will require additional support. Additional support is only required on select high value workload accelerators, fibre switches, InfiniBand and UPS options 12KVA and over. Coverage of the UPS battery is not included under TS support services; standard warranty terms and conditions apply.
Protect your business beyond warranty with HPE Support Services	HPE Technology Services delivers confidence, reduces risk and helps customers realize agility and stability. Connect to HPE to help prevent problems and solve issues faster. HPE Support Services enable you to choose the right service level, length of coverage and response time as you purchase your new server, giving you full entitlement to the support you need for your IT and business. Protect your product, beyond warranty.
Parts and Materials	Hewlett Packard Enterprise will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements. Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services. The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by Hewlett Packard Enterprise due to malfunction.
For more information	Visit the Hewlett Packard Enterprise Service and Support website.

Technical Specifications

General Specifications	Network Processor	Intel X550-AT2
	Data Rate	Two ports, each at 20 Gbps bi-directional; 40 Gbps bi-directional theoretical bandwidth.
	Bus type	PCIe 3 x4
	Form Factor	FlexibleLOM(562FLR-T) and Stand up (562T)
	IEEE Compliance	802.3ad, 802.3X, 802.1q, 802.1Qau, 802.1Qaz, 802.1Qbb, 802.1Qbg, IEEE1588, 802.1AS
	Connector	RJ-45 (two)
Power and Environmental Specifications	Power	10.50W typical, 14.50W maximum (562FLR-T) 11.15W typical, 15.56W maximum (562T)
	Temperature Operating	5° to 60° C (41° to 140° F)
	Temperature Non-Operating	-40°C to 70°C / -40°F to 158°F
	Humidity Operating	System relative humidity: Minimum to be the higher (more moisture) of -12°C (10.4°F) dew point or 8% relative humidity. Maximum to be the lower (less moisture) of 24°C (75.2°F) dew point or 90% relative humidity. Non-condensing.
	Humidity Non-operating	5 to 95% relative humidity, non-condensing.
	Other	PCIe 3.0 RoHS compliance 6 of 6 IPv4, IPv6 CE Microsoft WHQL (Windows Hardware Quality Labs)
	Operating System and Virtualization Support	The Operating Systems supported by this adapter are based on the server OS support. Please refer to the OS Support Matrix at https://www.hpe.com/us/en/servers/server-operating-systems.html .
	Environment-friendly Products and Approach - End-of-life Management and Recycling	Hewlett Packard Enterprise offers end-of-life <u>product return, trade-in, and recycling programs</u> , in many geographic areas, for our products. Products returned to Hewlett Packard Enterprise will be recycled, recovered or disposed of in a responsible manner. The EU WEEE Directive (2012/19/EU) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the <u>Hewlett Packard Enterprise web site</u> . These instructions may be used by recyclers and other WEEE treatment facilities as well as Hewlett Packard Enterprise OEM customers who integrate and re-sell Hewlett Packard Enterprise equipment.

Summary of Changes

Date	Version History	Action	Description of Change
02-Jul-2018	Version 5	Changed	Models and Compatibility sections were updated
07-May-2018	Version 4	Changed	Compatibility section was updated
05-Feb-2018	Version 3	Changed	Overview section was updated
16-Oct-2017	Version 2	Changed	Overview was updated.
25-Sep-2017	Version 1	Created	New QuickSpecs



© Copyright 2018 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

a00021588enw - 16045 - Worldwide - V5 - 02-July-2018