

Overview

****For latest information on this product please use [HPE Ethernet 10Gb SFP+ Adapters QuickSpecs](#)****

HPE Ethernet 10Gb 2-port 562SFP+ Adapter

Extended SKU - This adapter is part of an extended catalog of products tailored for customers in specific markets or with specific workloads, requiring the utmost in performance or value, but typically have a longer lead-time.

The HPE Ethernet 10Gb 2-port 562SFP+ Adapter features the latest Intel controller. It is a low-cost, low-power dual port PCIe v3.0 x8 adapter designed for HPE ProLiant servers. The HPE 562SFP+ addresses the demanding needs of the next-generation data center by providing unmatched features for virtualization and scalability that complement the HPE server platform.

The HPE 562SFP+ comes with both low profile and standard brackets and has two SFP+ cages that enable connections with DACs as well as SR fiber optic modules. The HPE 562SFP+ adapter supports SR-IOV and high performance networking features such as VLAN tagging, low latency interrupts, TCP and UDP checksum offloading, MSI-X, NIC teaming (bonding), Receive Side Scaling (RSS), jumbo frames, and PXE boot.



Overview



HPE Ethernet 10Gb 2-port 562SFP+ Adapter

Platform Information

Models

HPE Ethernet 10Gb 2-port 562SFP+ Adapter

727055-B21

Kit Contents	HPE Ethernet 10Gb 2-port 562SFP+ Adapter
	Quick install card
	Product warranty statement

Compatibility - Supported Servers	HPE ProLiant DL60 Gen9 Server
	HPE ProLiant DL80 Gen9 Server
	HPE ProLiant DL120 Gen9 Server
	HPE ProLiant DL160 Gen9 Server
	HPE ProLiant DL180 Gen9 Server
	HPE ProLiant DL360 Gen9 Server
	HPE ProLiant DL360 Gen10 Server
	HPE ProLiant DL380 Gen9 Server
	HPE ProLiant DL380 Gen10 Server
	HPE ProLiant DL385 Gen10 Server
	HPE ProLiant DL560 Gen9 Server
	HPE ProLiant DL580 Gen9 Server
	HPE ProLiant ML110 Gen9 Server
	HPE ProLiant ML150 Gen9 Server
	HPE ProLiant ML350 Gen9 Server
	HPE Apollo 2000 XL170r Gen9 Server
	HPE Apollo 2000 XL190r Gen9 Server
	HPE Apollo 4200 Gen9 Server
	HPE Apollo 4500 - XL450 Gen9 Server
	HPE Apollo 6000 - XL230a Gen9 Server
	HPE Apollo 6000 - XL250a Gen9 Server
	HPE Apollo 6000 - XL260a Gen9 Server
	HPE Apollo 6000 - XL270d Gen9 Server
	HPE Apollo 6500 - XL270d Gen10 Server

NOTE: This is a list of supported servers. Some may be discontinued.

Standard Features

At a Glance Features	Hardware acceleration TCP/IP/UDP stateless intelligent offloads Industry-leading throughput and latency performance Operates at 1 Gbps/10 Gbps, auto-negotiation, on both ports Up to 40 Gb/s bi-directional near line rate throughput Low profile design shipping with standard height and low-profile brackets On chip temperature monitor Integrated PHY and MAC Support for Preboot eXecution Environment (PXE) Supports SR-IOV (requires server FW, SW and OS support) PXE, Jumbo Frames, Checksum & Segmentation Offload, IPv6 and RSS Standard server operating system support Field replaceable and upgradeable IEEE 1588 (Time Synchronization) Standard NC series option kit warranty, support, services
Throughput-Theoretical Bandwidth	This adapter delivers 20 Gb/s bi-directional Ethernet transfer rate per port (40 Gb/s per adapter), providing the network performance needed to improve response times and alleviate bottlenecks.
802.1Q VLANs	IEEE 802.1Q virtual local area network (VLAN) protocol allows each physical port of this adapter to be separated into multiple virtual NICs for added network segmentation and enhanced security and performance. VLANs increase security by isolating traffic between users. Limiting the broadcast traffic to within the same VLAN domain also improves performance.
Checksum & Segmentation Offload	Normally the TCP Checksum is computed by the protocol stack. Segmentation Offload is technique for increasing outbound throughput of high-bandwidth network connections by reducing CPU overhead. The technique is also called TCP segmentation offload (TSO) when applied to TCP, or generic segmentation offload (GSO).
Configuration Utilities	This adapter ships with a suite of operating system-tailored configuration utilities that allow the user to enable initial diagnostics and configure adapter teaming. This includes a patented teaming GUI for Microsoft Windows operating systems. Additionally, support for scripted installations of teams in a Microsoft Windows environment allow for unattended OS installations.
DPDK	This adapter supports DPDK with benefit for packet processing acceleration and use in NFV deployments.

Standard Features

HPE Sea Of Sensors 3D	Support for the HPE Sea of Sensors which is a collection of 32 sensors that automatically track thermal activity - heat - across the server. When temperatures get too high, sensors can initiate fans and make other adjustments to reduce energy usage. A significant improvement lies in the ability to apply fan speed increases only to the portion of the system that is rising in temperature, rather than all six fans in unison, which reduces the amount of energy used for cooling.
IPv6	IPv6 uses 128-bit addressing allowing for more devices and users on the internet. IPv4 supported 32-bit addressing.
Jumbo Frames	This adapter supports Jumbo Frames (also known as extended frames), permitting up to a 9,000 byte (KB) transmission unit (MTU) when running Ethernet I/O traffic. This is over five times the size of a standard 1500-byte Ethernet frame. With Jumbo Frames, networks can achieve higher throughput performance and greater CPU utilization. These attributes are particularly useful for database transfer and tape backup operations.
LED Indicators	LED indicators show link integrity and network activity for easy troubleshooting.
Management Support	This adapter ships with agents that can be managed from HPE Systems Insight Manager or other management application that support SNMP.
Message Signaled Interrupt (Extended) (MSI-X)	Message Signaled Interrupt (Extended) provides performance benefits for multi-core servers by load balancing interrupts between CPUs/cores.
Network Adapter Teaming	This adapter support for NIC teaming helps IT administrators increase network fault tolerance and increased network bandwidth, the team of adapters can work together as a single virtual adapter, providing support for several different types of teaming enabling IT administrators to optimize availability, improve performance and help reduce costs.
Optimized for Virtualization	I/O Virtualization support for VMware NetQueue and Microsoft VMQ helps meet the performance demands of consolidated virtual workloads.
PCI Express Interface	This adapter is designed with an eight lane (x8) PCI Express bus based on the PCIe 3.0 standard. The adapter is backward compatible with four lane (x4) PCI Express, automatically auto-sensing between x8 and x4 slots.

Standard Features

Preboot eXecution Environment (PXE)	Support for PXE enables automatic deployment of computing resources remotely from anywhere. It allows a new or existing server to boot over the network and download software, including the operating system, from a management/ deployment server at another location on the network. Additionally, PXE enables decentralized software distribution and remote troubleshooting and repairs.
--	---

Receive Side Scaling (RSS)	RSS resolves the single-processor bottleneck by allowing the receive side network load from a network adapter to be shared across multiple processors. RSS enables packet receive-processing to scale with the number of available processors.
-----------------------------------	--

Server Integration	This adapter is a validated, tested, and qualified solution that is optimized for HPE ProLiant servers. Hewlett Packard Enterprise validates a wide variety of major operating systems drivers with the full suite of web-based enterprise management utilities including HPE Intelligent Provisioning and HPE Systems Insight Manager that simplify network management. This approach provides a more robust and reliable networking solution than offerings from other vendors and provides users with a single point of contact for both their servers and their network adapters.
---------------------------	---

TCP/UDP/IP	For overall improved system response, this adapter supports standard TCP/IP offloading techniques including: TCP/IP, UDP checksum offload (TCO) moves the TCP and IP checksum offloading from the CPU to the network adapter. Large send offload (LSO) or TCP segmentation offload (TSO) allows the TCP segmentation to be handled by the adapter rather than the CPU.
-------------------	--

Precision Time Protocol (IEEE 1588 PTP)	Synchronization of system clocks throughout a network, achieving clock accuracy in the sub-microsecond range, making it suitable for measurement and control systems.
--	---

VMware NewQueue and Microsoft Virtual Machine Queue (VMQ)	VMware NetQueue is technology that significantly improves performance of 10 Gigabit Ethernet network adapters in virtualized environments. Windows Hyper-V VMQ (VMQ) is a feature available on servers running Windows Server 2008 R2 with VMQ-enabled Ethernet adapters. VMQ uses hardware packet filtering to deliver packet data from an external virtual machine network directly to virtual machines, which reduces the overhead of routing packets and copying them from the management operating system to the virtual machine.
--	--

Warranty	Maximum: The remaining warranty of the HPE product in which it is installed (to a maximum three-year, limited warranty). Minimum: One year limited warranty. NOTE: Additional information regarding worldwide limited warranty and technical support is available at: http://h17007.www1.hpe.com/us/en/enterprise/servers/warranty/index.aspx#.V4e3tPkrJhE
-----------------	--

Service and Support

Service and Support **NOTE:** This adapter is covered under HPE Support Services/ Service Contract applied to the HPE ProLiant Server or enclosure. No separate HPE Support Services need to be purchased.

Most HPE branded options sourced from HPE that are compatible with your product will be covered under your main product support at the same level of coverage, allowing you to upgrade freely. Additional support is required on select workload accelerators, switches, racks and UPS options 12KVA and over. Coverage of the UPS battery is not included under HPE support services; standard warranty terms and conditions apply.

Warranty and Support Services

Warranty and Support Services will extend to include HPE options configured with your server or storage device. The price of support service is not impacted by configuration details. HPE sourced options that are compatible with your product will be covered under your server support at the same level of coverage allowing you to upgrade freely. Installation for HPE options is available as needed. To keep support costs low for everyone, some high value options will require additional support. Additional support is only required on select high value workload accelerators, fibre switches, InfiniBand and UPS options 12KVA and over. Coverage of the UPS battery is not included under TS support services; standard warranty terms and conditions apply.

Protect your business beyond warranty with HPE Support Services

HPE Technology Services delivers confidence, reduces risk and helps customers realize agility and stability. Connect to HPE to help prevent problems and solve issues faster. HPE Support Services enable you to choose the right service level, length of coverage and response time as you purchase your new server, giving you full entitlement to the support you need for your IT and business. Protect your product, beyond warranty.

Parts and Materials

Hewlett Packard Enterprise will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements. Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services. The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by Hewlett Packard Enterprise due to malfunction.

For more information

Visit the Hewlett Packard Enterprise Service and Support [website](#).

Related Options

Cables - Direct Attach	HPE BladeSystem c-Class 10GbE SFP+ to SFP+ 0.5m Direct Attach Copper Cable	487649-B21
	HPE BladeSystem c-Class 10GbE SFP+ to SFP+ 1m Direct Attach Copper Cable	487652-B21
	HPE BladeSystem c-Class 10GbE SFP+ to SFP+ 3m Direct Attach Copper Cable	487655-B21
	HPE BladeSystem c-Class 10GbE SFP+ to SFP+ 5m Direct Attach Copper Cable	537963-B21
	HPE FlexNetwork X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable	JD095C
	HPE FlexNetwork X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable	JD096C
	HPE FlexNetwork X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	JD097C
	HPE FlexNetwork X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable	JG081C
	HPE FlexNetwork X240 10G SFP+ SFP+ 7m Direct Attach Copper Cable	JC784C
	HPE X242 10G SFP+ to SFP+ 1m Direct Attach Copper Cable	J9281B
	HPE X242 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	J9283B
	Aruba 10G SFP+ to SFP+ 7m Direct Attach Copper Cable	J9285D
	HP X242 10G SFP+ to SFP+ 15m Direct Attach Copper Cable	J9287B
	NOTE: Direct Attach Cable (DAC) must be purchased separately for copper environments.	

Cables - Fiber Optic	HPE LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable	AJ833A
	HPE LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable	AJ834A
	HPE LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable	AJ836A
	HPE LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable	AJ837A
	HPE LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable	AJ838A
	HPE LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable	AJ839A
	NOTE: Fiber transceivers and cables must be purchased separately for fiber-optic environments.	

Transceivers	HPE BladeSystem c-Class 10Gb SFP+ SR Transceiver	455883-B21
	HPE BladeSystem c-Class 10Gb SFP+ LR Transceiver	455886-B21
NOTE: Fiber transceivers and cables must be purchased separately for fiber-optic environments.		

Technical Specifications

General Specifications	Network Processor	Intel® X710 Controller
	Data Rate	Two ports, each at 20 Gb/s bi-directional; 40 Gb/s aggregate bi-directional theoretical bandwidth.
	Onboard Memory	256 MB
	Bus type	PCI Express 3.0 at 8 GT/s x8
	Form Factor	Standard and low profile adapter compliant with the PCIe standard
	IEEE Compliance	802.3, 802.1ab, 802.3x, 802.3ad, 802.3p, 802.1q, 802.3ae, 802.1au, 802.3ap, 802.1as, 802.3ak,802.1qaz, 802.1Qbb
Power and Environmental Specifications	Power	10W typical, 10.8W maximum
	Temperature - Operating	0° to 55°C (32° to 131°F)
	Humidity - Operating	5% to 95% non-condensing
	Emissions	Class B
	Classification	
	Agency Approvals	USA: FCC Part 15 Class B Canada: ICES-003, Issue 5 Japan: VCCI 2011-04 Class B International: EN55022:2010 + Class B, EN55024:2010; EN61000-3-2:2006, EN61000-3-3:2008 Taiwan: BSMI, CNS13438 (2006) Class B Australia/New Zealand (AS/NZS): AS/NZS CISPR 22: 2009+A1:2010 Class Korea: KN22 Class B, KN24
Operating System and Virtualization Support	RoHS Compliance	5 of 6
	Safety	UL Mark (USA and Canada) CE Mark EN 605901 2nd edition
Environment-friendly Products and Approach - End-of-life Management and Recycling	Operating Systems supported by this adapter are based on the server OS support. Please refer to the OS Support Matrix at https://www.hpe.com/us/en/servers/server-operating-systems.html	
Environment-friendly Products and Approach - End-of-life Management and Recycling	Hewlett Packard Enterprise offers end-of-life product return, trade-in, and recycling programs , in many geographic areas, for our products. Products returned to Hewlett Packard Enterprise will be recycled, recovered or disposed of in a responsible manner.	
	The EU WEEE Directive (2012/19/EU) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard Enterprise web site . These instructions may be used by recyclers and other WEEE treatment facilities as well as Hewlett Packard Enterprise OEM customers who integrate and re-sell Hewlett Packard Enterprise equipment.	

Summary of Changes

Date	Version History	Action	Description of Change
07-May-2018	Version 9	Changed	Compatibility section was updated
05-Mar-2018	Version 8	Changed	At a Glance Features section was updated
05-Feb-2018	Version 7	Changed	Overview section was updated
18-Dec-2017	Version 6	Changed	Standard Features-At a Glance Features and Product Information- Compatibility were updated
16-Oct-2017	Version 5	Changed	Overview and Technical Specifications sections were updated.
11-Jul-2017	Version 4	Created	Compatibility section was updated.
10-Feb-2017	Version 3	Changed	Compatibility, Standard Features, Service and Support, Related Options, and Technical Specifications sections were updated.
		Removed	Change Obsolete SKUs were deleted: 453151-B21, 647594-B21, 615732-B21, 652497-B21, 652503-B21, 656596-B21, 665249-B21, 716591-B21, 718904-B21, 665240-B21, 647581-B21, 665243-B21, 700699-B21, 717491-B21, 700759-B21, 700751-B21.
07-Oct-2016	Version 2	Created	Add DPDK support
31-Mar-2016	Version 1	Created	New QuickSpecs



Sign up for updates



© Copyright 2018 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

c04605575 - 15242 - Worldwide - V9-07-May-2018